



BISCO® IF-200 Tear Resistant Specialty Silicone Foam

BISCO® IF-200 tear-resistant silicone foam consists of a fiberglass support layer directly bonded to BF-1000. The material is designed to provide resistance against tear and abrasion while retaining flexibility. It acts as a supportive base during mechanical installation and an insulator when the fiberglass side is against a hot surface.

Features & Benefits:

- BF-1000 foam bonded to fiberglass support layer
- Withstands harsh environments
- Good tear strength
- Supportive yet flexible base for installation

IF-200 – BF-1000 CAST ON FIBERGLASS

PROPERTY	TEST METHOD	TYPICAL VALUE	SPECIFICATION
PHYSICAL			
Color	Visual	White	---
Thickness, mm (inches)	Internal	5.00 (0.197)	---
Areal Density, kg/m ² (lb./ft ²)	Internal	1.42 (0.29)	< 1.71 (< 0.35)
Cohesive Failure	Internal	Pass	---
Flammability			
Burn Length	FMVSS302	Pass	4 in/min

Values in bold are tested on a batch basis. Further industry specifications tested in tables below.
For additional performance properties, please see BF-1000 Data Sheet.

Standard Thickness Tolerances IF-200

NOMINAL THICKNESS	TOLERANCE
mm (inches)	mm (inches)
5.00 (0.197)	± 0.762 (± 0.030)

Slit Material and Tape (PSA) Width Tolerances

NOMINAL WIDTH	TOLERANCE
mm (inches)	mm (inches)
> 0 - 76 (> 0 - 3)	± 1.60 (± 0.063)
> 76 - 203 (> 3 - 8)	± 2.39 (± 0.094)
> 203 - 305 (> 8 - 12)	± 3.18 (± 0.125)
> 305 - 457 (> 12 - 18)	± 4.78 (± 0.188)
> 457 - 660 (> 18 - 26)	± 5.56 (± 0.219)
> 660 - 914 (> 26 - 36)	+ 25.4/- 0 (+ 1/- 0)

VALUE ADDED OFFERINGS

- Adhesive (PSA) lamination
- Slit material/tapes

Notes:

- *Typical Value-Value is based on historical data. Please note the frequency of testing varies.
- Additional industry specifications are available. All other properties are based on industry standard guidelines.
- All metric conversions are approximate.
- Values should not be used for specification limits.



The information contained in this Data Sheet is intended to assist you in designing with Rogers' Elastomeric Material Solutions. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers BISCO products for each application. The Rogers logo, BISCO, and the BISCO logo are trademarks of Rogers Corporation or one of its subsidiaries. © 2003, 2019, 2020; 2023 Rogers Corporation. All rights reserved. 0823-PDF • Publication #180-050 www.rogerscorp.com